

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
7 July 2005 (07.07.2005)

PCT

(10) International Publication Number
WO 2005/060602 A2

- (51) International Patent Classification: **Not classified**
- (21) International Application Number:
PCT/US2004/041060
- (22) International Filing Date: 9 December 2004 (09.12.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/529,343 12 December 2003 (12.12.2003) US
- (71) Applicant (for all designated States except US): **SEME-QUIP, INC.** [US/US]; 34 Sullivan Road, Unit 21, Billerica, MA 01862 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **HORSKY, Thomas, N.** [US/US]; 816 Depot Road, Boxborough, MA 01719 (US). **MILGATE, Robert, W., III.** [US/US]; 2 Heath Heights, Gloucester, MA 01930 (US).
- (74) Agent: **WILLIAMS, John, N.**; Fish & Richardson P.C., 225 Franklin Street, Boston, MA 02110-2804 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— without international search report and to be republished upon receipt of that report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: CONTROLLING THE FLOW OF VAPORS SUBLIMATED FROM SOLIDS



(57) **Abstract:** A vapor delivery system for delivering a steady flow of sublimated vapor to a vacuum chamber comprises a vaporizer of solid material, a mechanical throttling valve, and a pressure gauge, followed by a vapor conduit to the vacuum chamber. The vapor flow rate is determined by both the temperature of the vaporizer and the setting of the conductance of the mechanical throttle valve located between the vaporizer and the vacuum chamber. The temperature of the vaporizer is determined by closed-loop control to a set-point temperature. The mechanical throttle valve is electrically controlled, e.g. the valve position is under closed-loop control to the output of the pressure gauge. In this way the vapor flow rate can be generally proportional to the pressure gauge output. All surfaces exposed to the vapor from the vaporizer to the vacuum chamber are heated to prevent condensation. A gate valve and a rotary butterfly valve are shown acting as the upstream throttling valve. Employing a fixed charge of solid material, the temperature of the vaporizer may be held steady for a prolonged period, during which the throttle valve is gradually opened from a lower conductance of its operating range as the charge sublimates. When a greater valve displacement is reached, the temperature is raised, to enable the valve to readjust to its lower conductance setting from which it can again gradually open as more of the charge is consumed.



WO 2005/060602 A2